

## Main Specifications

### ■ Superior Series

		XJ- S400UN	XJ- S400U	XJ- S400WN	XJ- S400W
Brightness <sup>*1</sup>		4,000 lumens			
Display system		DLP® chip x 1, DLP® system			
Display chip	Chip size	WUXGA 0.67 inches (Aspect ratio: 16:10)		WXGA 0.65 inches (Aspect ratio: 16:10)	
	Number of pixels	2,304,000 pixels (1,920 x 1,200)		1,024,000 pixels (1,280 x 800)	
Contrast ratio		20,000:1			
Vertical keystone correction		+30° (automatic), ±30° (manual)			
Projection lens		1.7X manual zoom, manual focus, F=2.33 to 3.03 / f=19.5 to 32.3			
Projected image size		30 to 300 inches			
Projection distance	60-inch	1.64 to 2.78 meters (5.4 to 9.1 feet)		1.72 to 2.92 meters (5.7 to 9.6 feet)	
	100-inch	2.80 to 4.70 meters (9.2 to 15.4 feet)		2.94 to 4.94 meters (9.7 to 16.2 feet)	
	Minimum projection distance	0.77 meters (2.5 feet)		0.81 meters (2.7 feet)	
Light source (estimated lifetime <sup>*2</sup> )		Laser & LED (up to 20,000 hours)			
Color reproduction		Full color (up to 1.07 billion colors)			
Scanning Frequencies		Horizontal: 15 to 91 kHz, Vertical: 50 to 85 Hz			
Computer input	Digital input terminal	HDMI Type A x 2			
	Analog input terminal	mini D-sub 15-pin x 2	mini D-sub 15-pin x 1	mini D-sub 15-pin x 2	mini D-sub 15-pin x 1
	Monitor out terminal	mini D-sub 15-pin x 1	---	mini D-sub 15-pin x 1	---
Video input	Analog input terminal	Component: YCbCr/YPbPr (used for both analog computer input and component input), Analog video: Composite (RCA) x1			
Audio	Input	3.5 mm stereo mini jack x 2, RCA x1 [R/L], 3.5 mm monaural mini jack (for Mic.) x 1 <sup>*3</sup>	3.5 mm stereo mini jack x 1, RCA x1 [R/L]	3.5 mm stereo mini jack x 2, RCA x1 [R/L], 3.5 mm monaural mini jack (for Mic.) x 1 <sup>*3</sup>	3.5 mm stereo mini jack x 1, RCA x1 [R/L]
	Output	3.5 mm stereo mini jack x 1 (variable audio)			
	Speaker	16W x 1, monaural			
Other Terminals	USB host	USB 2.0 Type-A x 2	---	USB 2.0 Type-A x 2	---
	USB power supply	DC 5V (Shared with USB host terminal)	DC 5V USB Type-A x 1 (Dedicated power supply terminal)	DC 5V (Shared with USB host terminal)	DC 5V USB Type-A x 1 (Dedicated power supply terminal)
	USB function	USB 1.1 Micro-B x 1 <sup>*4</sup>			
	Control (serial)	RS-232C (D-Sub 9 pin) x 1			
	LAN	RJ-45 x 1	---	RJ-45 x 1	---
Wireless LAN support	IEEE 802.11 b/g/n <sup>*5</sup> (requires separately available YW-41 wireless LAN adaptor)	---	IEEE 802.11 b/g/n <sup>*5</sup> (requires separately available YW-41 wireless LAN adaptor)	---	
Power requirements	AC 100 to 240V, 50/60Hz				
Approximate dimensions (W x H x D)	357 x 124 x 337 mm (excluding protruding parts) 14.1 x 4.9 x 13.3 inches (excluding protruding parts)				
Security Compatibility	Kensington-compatible, Security bar, Power-on password				
Included Accessories <sup>*6</sup>	Remote control, Power cord, Warranty card				

\*1. When using Bright mode.

\*2 Lifetime not guaranteed.

\*3 Plug-in power microphones are not supported.

\*4 For firmware updates and logo data registration.

\*5 With connection of wireless LAN adaptor to USB-A (Host) port.

\*6 User and Network manuals available for downloading from the CASIO website after the products are launched.

DLP is a registered trademark of Texas Instruments of the United States.

Other company and product names are generally registered trademarks or trademarks of their respective companies.x1

■ Advanced Series

		XJ- F211WN	XJ- F21XN	XJ- F101W	XJ- F11X
Brightness <sup>*1</sup>		3,500 lumens	3,300 lumens	3,500 lumens	3,300 lumens
Display system		DLP® chip x 1, DLP® system			
Display chip	Chip size	WXGA 0.65 inches (Aspect ratio: 16:10)	XGA 0.55 inches (Aspect ratio: 4:3)	WXGA 0.65 inches (Aspect ratio: 16:10)	XGA 0.55 inches (Aspect ratio: 4:3)
	Number of pixels	1,024,000 pixels (1,280 x 800)	786,432 pixels (1,024 x 768)	1,024,000 pixels (1,280 x 800)	786,432 pixels (1,024 x 768)
Contrast ratio		20,000:1			
Vertical keystone correction		+30° (automatic), ±30° (manual)			
Projection lens		1.5X manual zoom, manual focus, F=2.31 to 2.73 / f=18.9 to 27.2			
Projected image size		35 to 300 inches	30 to 300 inches	35 to 300 inches	30 to 300 inches
Projection distance	60-inch	1.64 to 2.42 meters (5.4 to 7.9 feet)	1.95 to 2.87 meters (6.4 to 9.4 feet)	1.64 to 2.42 meters (5.4 to 7.9 feet)	1.95 to 2.87 meters (6.4 to 9.4 feet)
	100-inch	2.81 to 4.11 meters (9.2 to 13.5 feet)	3.33 to 4.85 meters (10.9 to 15.9 feet)	2.81 to 4.11 meters (9.2 to 13.5 feet)	3.33 to 4.85 meters (10.9 to 15.9 feet)
	Minimum projection distance	0.92 meters (3.0 feet)	0.93 meters (3.1 feet)	0.92 meters (3.0 feet)	0.93 meters (3.1 feet)
Light source (estimated lifetime <sup>*2</sup> )		Laser & LED (up to 20,000 hours)			
Color reproduction		Full color (up to 1.07 billion colors)			
Scanning Frequencies		Horizontal: 15 to 91 kHz, Vertical: 50 to 85 Hz			
Computer input	Digital input terminal	HDMI Type A x 2			
	Analog input terminal	mini D-sub 15-pin x 1			
Video input	Analog input terminal	Component: YCbCr/YPbPr (used for both analog computer input and component input), Analog video: Composite (RCA) x1			
Audio	Input	3.5 mm stereo mini jack x 1, RCA x1 [R/L] 3.5 mm monaural mini jack (for Mic.) x 1 <sup>*3</sup>		3.5 mm stereo mini jack x 1, RCA x1 [R/L]	
	Output	3.5 mm stereo mini jack x 1 (variable audio)			
	Speaker	16W x 1, monaural			
Other Terminals	USB host	USB 2.0 Type-A x 1		---	
	USB power supply	DC 5V (Shared with USB host terminal)		DC 5V USB Type-A x 1 (Dedicated power supply terminal)	
	USB function	USB 1.1 Micro-B x 1 <sup>*4</sup>			
	Control (serial)	RS-232C (D-Sub 9 pin) x 1			
	LAN	RJ-45 x 1		---	
Wireless LAN support		IEEE 802.11 b/g/n <sup>*5</sup> (requires separately available YW-41 wireless LAN adaptor)		---	
Power requirements		AC 100 to 240V, 50/60Hz			
Approximate dimensions (W x H x D)		299 x 97 x 299 mm (including protruding parts) (11.8 x 3.8 x 11.8 inches (including protruding parts))			
Approximate weight		3.8 kg (8.4 lb)			
Security Compatibility		Kensington-compatible, Security bar, Power-on password			
Included Accessories <sup>*6</sup>		Remote control, Power cord, Warranty card			

\*1. When using Bright mode.

\*2 Lifetime not guaranteed.

\*3 Plug-in power microphones are not supported.

\*4 For firmware updates and logo data registration.

\*5 With connection of wireless LAN adaptor to USB-A (Host) port.

\*6 User and Network manuals available for downloading from the CASIO website after the products are launched.

DLP is a registered trademark of Texas Instruments of the United States.

Other company and product names are generally registered trademarks or trademarks of their respective companies.x1

■ Ultra-Short Throw Series

		XJ-UT352WN	XJ-UT352W	XJ-UT312WN
Brightness <sup>*1</sup>		3,500 lumens	3,500 lumens	3,100 lumens
Display system		DLP® chip x 1, DLP® system		
Display chip	Chip size	WXGA 0.65 inches (Aspect ratio: 16:10)		
	Number of pixels	1,024,000 pixels (1,280 x 800)		
Contrast ratio		20,000:1		
Horizontal and vertical keystone correction		± approx. 5° (manual)		
Projection lens		Fixed zoom, manual focus, F=2.3 / f=4.2		
Projected image size		50 to 110 inches		
Projection distance	60-inch	0.13 m (0.4 ft)		
	100-inch	0.4 m (1.3 ft)		
	Minimum projection distance	0.06 m (0.2 ft)		
Light source (estimated lifetime <sup>*2</sup> )		Laser & LED (up to 20,000 hours)		
Color reproduction		Full color (up to 1.07 billion colors)		
Scanning Frequencies		Horizontal: 15 to 91 kHz, Vertical: 50 to 85 Hz		
Computer input	Digital input terminal	HDMI Type A x 2		HDMI Type A x 1
	Analog input terminal	mini D-sub 15-pin x 2		
Video input	Analog input terminal	Component: YCbCr/YPbPr (used for both analog computer input and component input), Analog video: Composite (RCA) x1		
Audio	Input	3.5 mm stereo mini jack x 2, RCA x1 [R/L] 3.5 mm monaural mini jack (for Mic.) x 1 <sup>*3</sup>		
	Output	3.5 mm stereo mini jack x 1		
	Speaker	16W x 1, monaural		
Other Terminals	USB host	USB 2.0 Type-A x 2	---	USB 2.0 Type-A x 2
	USB power supply	DC 5V (Shared with USB host terminal)	DC 5V USB Type-A x 1 (Dedicated power supply terminal)	DC 5V (Shared with USB host terminal)
	USB function	USB 1.1 Micro-B x 1 <sup>*4</sup>		
	Control (serial)	RS-232C (D-Sub 9 pin) x 1		
	LAN	RJ-45 x 1	---	RJ-45 x 1
Wireless LAN support		IEEE 802.11 b/g/n <sup>*5</sup> (requires separately available YW-41 wireless LAN adaptor)	---	IEEE 802.11 b/g/n <sup>*5</sup>
Power requirements		AC 100 to 240V, 50/60Hz		
Approximate dimensions (W x H x D)		338 x 141 x 333 mm (excluding protruding parts)		
Approximate weight		5.8 kg (12.8 lb)		
Security Compatibility		Kensington-compatible, Security bar, Power-on password		
Included Accessories <sup>*6</sup>		Remote control, Power cord, Warranty card, Wireless LAN adaptor (only for XJ-UT312WN)		

\*1. When using Bright mode.

\*2 Lifetime not guaranteed.

\*3 Plug-in power microphones are not supported.

\*4 For firmware updates and logo data registration.

\*5 With connection of wireless LAN adaptor to USB-A (Host) port.

\*6 User and Network manuals available for downloading from the CASIO website after the products are launched.

DLP is a registered trademark of Texas Instruments of the United States.

Other company and product names are generally registered trademarks or trademarks of their respective companies.x1